



Supreme Gypsum Pvt. Ltd.

MANUFACTURES OF QUALITY GYPSUM PLASTERS

Apurva House, Opp. Ram Nivas, Pai Nagar, S. V. P. Road, Borivali (W). Mumbai – 400092.

Tel.: 022 – 42361616 / Tel. Fax: 022 – 42361617.

Email : supremegypsum@airtelmail.in / Website : www.supremegypsum.net

SUPER BIND PLUS PLUS SPECIFICATIONS & APPLICATION PROCEDURE

Supreme Gypsum Pvt.Ltd. has launched its new product **SUPER BIND PLUS** in Indian market keeping in mind ever changing new Technologies in construction fields. Super Bind Plus is a special product introduced to avoid the risk of debonding of Plasters from the newly introduced technique of precasted & Smooth concrete surfaces, which is commonly used today in construction world.

Super Bind Plus is a Cement based binder which gives tremendous binding strength to the Gypsum & keeps away the worry of material leaving the surface keeping ugly marks & tensions to the customers.

Advantages

- 1 Bonds most common construction materials
- 2 Improves the durability of mortars & renders
- 3 Excellent as a dust proofer & sealer
- 4 Easy application by Trowel or Spray machines.
- 5 Versatile & Economical

Description

Super Bind Plus multipurpose adhesive is ready to use product. In case if found less viscosity to be mixed with water as per the requirement of bringing the materials up to brushable level or Roller.

Properties

Appearance	Liquid
Colour	Green
Coverage	Up to 0.4mm thickness 35 to 40 sq.ft.per kg. Approx 40 sqf.
Applying	Single Coat only.

Preperation

Clean the surface & remove any dust,unbond or contaminated material, plaster ,oil, grease, corrosion deposits or algey formations. Oil & grease deposits if any should be removed by steam cleaning, detergent scrubbing or proprietary degreaser.

Application

Super Bind Plus, should be taken out in clean pot. If viscosity is higher & cannot be easily brushed or Roller than add some water in bare minimum quantity to be added into the material to reduce the viscosity & reduce it to the brushable level & now. Super Bind Plus is ready for use on the surfaces like smooth concrete or any other smooth surface.

Super Bind Plus, is to be applied with the help of brush or can be Rolled with cotton roller on to the surface to the surface.

After application of the Super Bind Plus, on the surface, leave the surface for minimum 24 hours before application of Gypsum on it

Benefits

As a plaster bonding agent it reduces hacking & keying, also it will provide an adhesive or mechanical key to receive plaster or render coats of Gypsum, light weight Gypsum or anhydrous plasters, plastering on tiles etc.

Company stands warranty against debonding of Super Bond from the surfaces if it is used strictly in accordance to the specifications.

For SUPREME GYPSUM PVT. LTD.

for
Director Tech.