



Supreme Gypsum Pvt. Ltd.

MANUFACTURES OF QUALITY GYPSUM PLASTERS

Apurva House, Opp. Ram Nivas, Pai Nagar, S. V. P. Road, Borivali (W). Mumbai – 400092.

Tel.: 022 – 42361616 / Tel. Fax: 022 – 42361617.

Email : supremegypsum@airtelmail.in / Website : www.supremegypsum.net

SUPER SMOOTH SPECIFICATIONS & APPLICATION PROCEDURE

Supreme Gypsum Pvt.Ltd. has launched its new product **SUPERSMOOTH** in Indian market keeping in mind ever changing new Technologies in construction fields. Super Smooth is a special product introduced to replace the traditional Putty or Neeru finish with Silky smooth & milky white finish

Super Smooth is a Cement based wall covering which gives tremendous binding strength with the Concrete surface & keeps away the worry of material leaving the surface keeping ugly marks & tensions to the customers.

Advantages

- 1 Bonds most common construction materials
- 2 Improves the durability of mortars & renders
- 3 Excellent water resistance
- 4 Easy application by Trowel or hand application.
- 5 Versatile & Economical

Description

Super Smooth multipurpose adhesive is to be mixed water in 1: 0.5 ratio i.e. 1 part of Super Smooth to be added to 0.5 parts of water.

Properties

Appearance	Powder form
Colour	Milky White
Compatibility with Cement	Can be used with all types of Portland Cement internal as well as external surface
Mesh Size	300 Mesh
Eco Friendly	Yes
Coverage	8 to 10 sft in 1 kg 200 to 250 sft in 25 kg bag.

Preparation

Clean the surface & remove any dust, unbond or contaminated material, plaster, oil, grease, corrosion deposits or algey formations. Oil & grease deposits if any should be removed by steam cleaning, detergent scrubbing or proprietary de-greaser.

Application

Super Smooth should be mixed in a clean pot with Tap water free from any contamination, quantity to be assessed as per requirement & work force available to carry out the work smooth & fast. Super Smooth is to be added to the water & not the water to Super Smooth as it may result in strength loss, mix it properly once again & now it is ready for use on the surfaces like Smooth concrete or any other Concrete surface.

Super Smooth is to be applied with the help of a trowel or by hand on the surface prepared. If the application is done by hand, it is strongly recommended that the workers should use hand gloves to avoid effects of heat release.

Once the material is applied on to the concrete, it is to be smoothened by 360 no. sanding paper for best effect. On such prepared surface any required paint can be applied.

Precautions

Use tap water only to avoid contamination

The pots used to mix the putty should also be free from dust & contamination.

Always add powder to water & not the water to powder.

The surface should be free from any dust particles or loose mortar.

Surface should be kept free from contact of water to avoid peeling off.

Coverage

The application on concrete surface should cover 200 to 250 sft in 2 coats of 0.5 to 0.75mm each, total thickness not exceeding 1.5mm depending upon the quality of surface.

Benefits

As a replacement of traditional wall caring Super Smooth proves strong & long lasting solutions with solid adhesion to all concrete surfaces like foam finish plasters which have been recently introduced in Indian market. It gives milky white finish & silky smooth finish so that the surface is ready to accept all kinds of decorations on to it.

Company stands warranty against peeling of Super Smooth from the surfaces if it is used strictly in accordance to the specifications.

For **Supreme Gypsum Pvt. Ltd.**

for
Director Tech.